



### Application

For use in gas wells and high-ratio oil wells where greater sealing efficiency is needed.

### Features

Two sets of Mini-flex seals (16 interlocking pads) offer greater sealing capability. Available with bypass and in special materials where CO<sub>2</sub> or H<sub>2</sub>S is present.

### Benefits/Advantages

The Duo-Flex is able to travel with less pressure and with less gas slippage. Often used with an internal bypass, allowing it to fall faster in liquids.

### New intelligence in problem solving™

The Duo-Flex Plunger is another low-cost, efficient method of increasing and optimizing production in oil and gas wells that have marginal flow characteristics.



### Features:

- Sixteen interlocking stainless steel pads
- "Flex" pads
- Available with or without a bypass system
- Superior seal for weaker wells

### Technical Specifications

Size	1¼	1½	21/16	23/8	27/8	3
Part #	—	—	—	PIG20T10	PIG25T10	PIG30T10
Overall Length	—	—	—	16.215"	16.215"	16.215"
O.D. (Max.)	—	—	—	2.000"	2.450"	2.936"
O.D. (Min.)	—	—	—	1.850"	2.250"	2.750"
Fishing Neck Size	—	—	—	13/8"	13/8"	13/8"
Weight	—	—	—	9.88 lbs.	14.6 lbs.	17.4 lbs.

Contact us today to learn how Plunger Lift Technology can help improve your production performance. Visit our web site or email us at: [staff@fbdoover.com](mailto:staff@fbdoover.com)

P.O. Box 130158

Tyler, TX 75713

(903) 561-4851

fax (903) 561-6567

[www.fbdoover.com](http://www.fbdoover.com)