

# iNodes™ Wireless Pressure Monitor (WPM)



**FERGUSON  
BEAUREGARD™**  
New Intelligence In Problem Solving™

## iNodes™ Wireless Pressure Monitor

The iNodes Wireless Pressure Monitor (WPM) is a pressure and temperature monitor that provides an economical method for remote measurement and alarming. The WPM is a self-contained battery powered, solar charged system for Class I, Division 1 hazardous locations which utilizes a permit free radio system for data communications. The WPM provides both remote data reporting and internal logging for convenient trending. Alarm cry-outs are provided for user-settable pressure and temperature conditions as alerts to problems or lost production. The WPM is field configurable and easy to calibrate.



### Features:

- Very low power consumption, solar powered with rechargeable battery storage
- Small, integrated package includes power supply, data storage, processing and communications
- Field configuration, software upgrade and local data retrieval by any iMonitoring-enabled PC, including laptop PCs and PDAs
- Rugged enclosure (IP65)
- Intrinsically safe (UL Class 1, Div. 1, Groups C and D) Temperature Code T4
- User configurable flow and process alarms
  - Alarms can be forwarded to the customer via telephone or email (requires optional alarm service)
  - Alarm holdoff prevents multiple alarm notification, minimizing notification cost
- Data can be secured with cypher encryption

## Technical Specifications

Environmental	
<b>Operating Temperature</b>	-40°C to +60°C (-40°F to 140°F)
<b>Storage Temperature</b>	-40°C to +70°C (-40°F to +158°F)
<b>Humidity</b>	5 to 95% RH, non-condensing
Measurement	
<b>Pressure</b>	<ul style="list-style-type: none"> <li>• Ranges: 0-75 psig, 0-500 psig, 0-1,500 psig, 0-3,600 psig, 0-6,000 psig, 0-10,000 psig (future)</li> <li>• Resolution: 0.05% Full Scale (FS)</li> <li>• Accuracy: ± 1% FS</li> </ul>
<b>Temperature</b>	<ul style="list-style-type: none"> <li>• Sensor: 100 platinum RTD</li> <li>• Range: -50°C to +100°C (-58°F to +212°F)</li> <li>• Resolution: 0.1°C (0.2°F)</li> <li>• Accuracy: + 1°C (+ 2°F)</li> </ul>
Alarms	
<b>Pressure</b>	User-settable low / high setpoint
<b>Temperature</b>	User-settable low / high setpoint with optional RTD
<b>Alarm Holdoff</b>	User-settable, 0 to 1,440 minutes (1 day)
Logging	
<b>Log Interval</b>	Every one minute or every five minutes (configurable)
<b>Maximum Log Depth</b>	<ul style="list-style-type: none"> <li>• 10 days in one minute mode</li> <li>• 50 days in five minute mode</li> </ul>
<b>Data Reported and Logged</b>	<ul style="list-style-type: none"> <li>• Entry date/time</li> <li>• Instantaneous pressure</li> <li>• Instantaneous temperature</li> <li>• Last day/hour avg, min, max pressure</li> <li>• Last day/hour avg, min, max temperature</li> <li>• Energy level</li> <li>• Device (alarm) status</li> </ul>

P.O. Box 130158  
Tyler, TX 75713  
(903) 561-4851  
fax (903) 561-6567  
www.fbdover.com

# iNodes™ Wireless Pressure Monitor (WPM)



**FERGUSON  
BEAUREGARD™**  
New Intelligence In Problem Solving™

## The iNodes™ Suite of Products Include:

- Tank Level Monitor
- Wireless Data Switch
- Electronic Flow Monitor
- Wireless Pressure/ Temperature Monitor
- Concentration & Communications Unit
- Concentration & Communications Unit – Remote Terminal Unit
- Compact Flash Radio
- Universal Serial Bus Radio

## Communications

<b>Protocol</b>	iMonitoring proprietary Frequency Hopping Spread Spectrum (FHSS)
<b>Certifications</b>	FCC Part 15.247, CFR 47 Part 15
<b>Service</b>	Half-Duplex
<b>Frequency</b>	902 - 928 MHz
<b>Antenna</b>	Standard 1/2 wave omni or optional 6 dBd Yagi
<b>Range</b>	<ul style="list-style-type: none"><li>• To CCU:<ul style="list-style-type: none"><li>• 1,500 feet typical line of sight</li><li>• Up to 5,000 feet (with optional high gain antennas)</li></ul></li><li>• To iMonitoring-enabled PC or PDA: 500 feet</li></ul>

## Power

<b>Source</b>	Solar panel, 0.25W standard. Optional 1W remote solar panel (remote power supply)
<b>Storage</b>	<i>Battery:</i> <ul style="list-style-type: none"><li>• Type: Rechargeable 3.6VDC lithium-ion</li><li>• Life: &gt; 5 years (typical)</li></ul>

## Mechanical

<b>Enclosure</b>	<ul style="list-style-type: none"><li>• <i>Ingress protection:</i> Meets IEC IP65 (dust and blowing rain)</li><li>• <i>Enclosure venting:</i> GORE™ protected vent</li></ul>
<b>Mounting</b>	<ul style="list-style-type: none"><li>• 1/2-inch NPT-M</li><li>• <i>Overpressure:</i> 1.5 x FS</li><li>• <i>Burst Pressure:</i> 6 x FS</li><li>• <i>Mounting for 0-75, 0-3,600, and 0-6,000:</i> 1/2-inch NPT</li><li>• <i>Mounting for 0-500 and 0-1,500:</i> 1/4-inch NPT</li></ul>

## Regulatory Approvals

<b>Safety</b>	UL and c-UL, Class I, Division 1, Groups C and D, temperature code T4 (Intrinsically safe)
<b>Communications</b>	Meets FCC Part 15.247 and Code of Federal Regulations (CFR) 47, Part 15



Contact us today to learn how iNodes Technology can help improve your production performance. Visit our web site or email us at: [staff@fbdoover.com](mailto:staff@fbdoover.com)

P.O. Box 130158  
Tyler, TX 75713  
(903) 561-4851  
fax (903) 561-6567  
[www.fbdoover.com](http://www.fbdoover.com)